



Solenoid valve 2/2 way N.O. **Direct acting** **Explosion proof - Atex Ex d**

21A3ZIV15D
 ÷
 21A2ZIV30D

PRESENTATION:

Direct acting S.V. for interception of fluids compatible with the construction materials. Aluminium coil housing, explosion proof "Ex d". Electrical and electromechanical components according to Atex Directive 2014/34/EU.

Minimum operational pressure is not required.


The materials used and the tests carried out ensure maximum reliability and duration.

USE: Potentially explosive atmospheres
 Zone 1, 2, 21, 22

PIPES: G 1/8 - G 1/4


COIL: 8W - Ø 13
 BDV 180°C (class H)

Max. allowable pressure (PS) 40 bar
 Housing ambient temperature - 40°C + 60°C



Gaskets	Temperature		Medium
V=FKM (fluoroelastomer)	- 10°C	+ 80°C	Mineral oils (2°E), gasoline gas oil, fuel oils (7°E)
F=H-NBR (hydrogenated nitrile)	- 30°C	+ 80°C	Air, inert gas, water R 134a, R 404a

For seals other than FKM replace the letter "V" with the ones corresponding to the other seals. E.I. 21A2ZIV20D.



Pipe ISO 228/1	Code	Max viscosity		Ø mm	Kv l/mn	Power watt	Pressure		
		cSt	°E				min bar	M.O.P.D.	
G 1/8	21A3ZIV15D	12	~ 2	1,5	1,4	8	0	25	25
	21A3ZIV20D	37	~ 5	2	2			20	20
	21A3ZIV25D	53	~ 7	2,5	3,2			14	14
	21A3ZIV30D			3	4			10	10
G 1/4	21A2ZIV15D	12	~ 2	1,5	1,4			25	25
	21A2ZIV20D	37	~ 5	2	2			20	20
	21A2ZIV25D	53	~ 7	2,5	3,2			14	14
	21A2ZIV30D			3	4			10	10




(According to Directive 2014/34/EU ATEX)
 II 2G Ex d IIC T6 or T5 Gb
 II 2D Ex tb IIIC T80°C or T95°C Db IP67

Note

Also available with brass body without lead | Available on request and with minimum quantities.

The "ODE " reserves the right to carry out technical and aesthetic modifications without prior notice.



MATERIALS:

Body	Brass - UNI EN 12165 CW617N
Armature tube	Stainless steel AISI series 300
Fixed core	Stainless steel AISI series 400
Plunger	Stainless steel AISI series 400
Phase displacement ring	Copper - Cu 99,9%
Spring	Stainless steel AISI series 300
Seal	Standard: V=FKM On request: F=H-NBR
Orifice: Insert slot	Stainless steel AISI series 300
Coil housing:	Die cast and passivated Aluminium

Connector conformity ISO 4400

FEATURES:

Electrical conformity	IEC 335
Protection degree	IP 67 EN 60529 (DIN 40050) if installed with cable gland Atex Ex d IP67 or higher.

SPARE PARTS:


1. Coil:

See coils list for
Solenoid valves explosion
proof Atex - Ex d

ACCESSORIES:

Code P992219 Cable Gland
(to be ordered separately)

DIMENSIONS:



COIL TYPE	POWER ABSORPTION		
	W	Hold VA ~	Inrush VA ~
B	8	14,5	25